

# INSTALLATION INSTRUCTIONS

# NOTES

- Installation should be completed by an individual familiar with the construction and operation of the luminaire.
- Installation of luminaire must be in accordance with nation and local building and electrical codes.
- Carefully read and follow all warnings and instructions before installing or servicing the luminaire.
- Instructions do not cover all details and all possible product configurations.
- Do not restrict luminaire ventilation.
- Ensure LED luminaire is not covered with material that will prevent convection or conduction cooling.
- Do not exceed luminaire's maximum ambient temperature.
- Ensure LED luminaire has the correct polarity before installation.

# **WARNINGS**

### **Electrical shock:**

- Disconnect or turn off power before installing or servicing luminaire.
- All electrical wiring to be completed by a qualified licensed electrician in accordance with local and National Electrical Code.
- Ensure supply voltage corresponds with the correct ballast/driver voltage.
- Avoid exposing wiring to metal edges and sharp objects
- Ensure that the luminaire is properly grounded to prevent electric hazards.

### Fire:

- Keep flammable and combustible materials away from the light source and/or lens.
- Use correctly rated supply conductors as indicated by product labeling.

#### Burn:

Allow luminaire to cool before handling luminaire.

# Personal Injury:

- Wear safety glasses and gloves when handling the luminaire to avoid physical injury.
- Avoid direct eye contact with light source.
- Always support the weight of the luminaire.

Manufacturers is not responsible for any injuries due to the improper installation or handing of its products.

### **INSTALLATION STEPS**


- Prepare for installation:
  - Read instructions thoroughly
  - Unpack and inspect for damaged or missing parts
  - Read fixture cautionary labels and markings
- Ceiling cutout:
  - Confirm ceiling compatibility and cutout size from technical drawings on product spec sheet Mark cutout locations
  - Perform cutout per manufacturer's instruction with appropriate tools minding cutout tolerances and straightness
  - Inspect cutout for imperfections, burrs, or other problems
- Assemble in ceiling: 3
  - Prepare top side mounting by cleaning and then laying a bead of silicone sealant around the underside flange of the housing before mechanically securing in place with approved fasteners



Secure with ceiling manufacturer-approved hardware (by others) to the ceiling panel's

exterior side

- Sandwich the ceiling with the door frame and housing as shown in below section view
- From the room-side, push the studs of the door frame through alignment holes of the housing then fasten nuts from the service side (may require an extra person for this part)
- Align and tighten the \( \frac{1}{4} \) -20 nuts to draw the door frame assembly towards the ceiling until lightly touching
- Slowly tighten nuts in a staggered pattern until housing and door frame are firmly secured in ceiling



- Install top cover and make electrical connections
- 5. Energize and inspect

# KURTZON™

1420 S. Talman Avenue Chicago, IL 60608 Website: www.kurtzon.com Phone: 773.277.2121